

PERSONAL PROTECTION EQUIPMENT IN ACCORDANCE TO NF EN ISO 20471 (2013)

INSTRUCTIONS

GENERAL PROTECTION

This is an article of Personal Protection Equipment conforming to the standards prescribed in EN ISO 20471 (2013) . It was the focus of a CE exam of the type performed by Centexbel n°0493 – Technologiepark 7 – 9052 Zwijnaarde – Belgium, notified organization.

Wearing this uniform takes into account the practice of basic safety and caution measures.

The uniform should be worn sealed from top to bottom. It should be visible at all times and should therefore not be covered by another article that does not conform to the standards prescribed EN ISO 20471.

This uniform is visible in all lighting conditions of the day, nighttime, and headlights.

Any modifications to the uniform (length or accessories) can only be done by the written consent of the company ELIS, in accordance with the options available in the rules.

WARNING:

This equipment is not authorized as rain gear.

It should be properly stored, either folded flat or suspended on a hanger in a dry place not exposed to light. It will be delivered in a plastic bag.

Putting the equipment through a finishing cycle of 160°C should have no effect on the lifespan of the material, as long as the standard procedures of regular industrial washing are respected, particularly in regards to the humidity at the entrance of the tunnel and the actual temperature of the tunnel.

This equipment has a lifespan of 50 washings if the care instructions printed on the tag located on the inside of the article are strictly followed.

The clothing does not contain toxic substances or substances which damage health.

A regular check of the clothing is recommended in order to prevent damage or evidence of ageing. If needed, the clothing must be repaired or replaced

High-visibility signaling uniform

- x **HIGH-VISIBILITY SIGNALLING UNIFORM**
 x: Class relative to surface with fluorescent and reflective material
 y : Class relative to photometric requirements of reflective material

MINIMUM SURFACES IN M ²	Class 3	Class 2	Class 1
Base material	0.80	0.50	0.14
Reflective material	0.20	0.13	0.10
Combined characteristics material	-	-	0.20

3 Uniform including jacket +
 2 trousers worn simultaneous
 EN ISO 20471-2013



Wash at maximum temperature of 75°C



Do not bleach



Tumble drying possible

2 Jacket or trousers worn
 separately
 2
 EN ISO 20471-2013



Iron at maximum temperature of 150°C

Do not dry clean